


.100	Header	Single Row - Stacking	Rt Angle	Thru Hole
------	--------	-----------------------	----------	-----------

.100 inch Center - .025 inch Square Pin - Board Stacking - Single Row Right Angle Header



Base Part Number	A		B		C		D		E		Plating Options	Number of Positions
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch		
5602	4.06	0.160	5.84	0.230	3.94	0.155	5.08	0.200	5.84	0.230	G2LF : TLF	2-40
5603	4.06	0.160	5.84	0.230	3.94	0.155	7.62	0.300	5.84	0.230	G2LF : TLF	2-40

Technical Notes	
Contact Material:	Pin: Phosphor Bronze - .025 inch sq pin - burr free both ends
Insulation Material:	Glass Filled Nylon 46 - UL 94V-0 rated - Black (std)
Heat Deflection:	260°C @ 264 PSI per ASTM D648
Insulation Resistance:	5000 MegOhm @ 500VDC
Current Rating:	3 amps continuous @ 100 VDC/contact
Max Processing Temp:	250°C for 60 seconds
Plastic:	High Temperature Plastic
INTERCONNECT SYSTEMS INC.	
741 Flynn Road, Camarillo, Ca 93012 · (805) 482-2870 · fax (805) 482-8470 · e-mail: info@isipkg.com	