


<b>.100</b>	<b>Header</b>	<b>Double Row - High Profile</b>	<b>Rt Angle</b>	<b>Thru Hole</b>
-------------	---------------	----------------------------------	-----------------	------------------

.100 inch Center - .025 inch Square Pin - High Profile - Double Row Right Angle Header



Base Part Number	A		B		C		D		E		Plating Options	Number of Positions
	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch		
<b>4720R</b>	1.52	0.060	3.05	0.120	5.84	0.230	5.84	0.230			G2LF : G1 : TLF	4-80
<b>4721R</b>	1.52	0.060	3.30	0.130	8.08	0.318	5.84	0.230			G2LF : G1 : TLF	4-80
<b>4722R</b>	1.52	0.060	3.30	0.130	10.67	0.420	5.84	0.230			G2LF : G1 : TLF	4-80

Technical Notes	
<b>Contact Material:</b>	Pin: Phosphor Bronze - .025 inch sq pin - burr free both ends
<b>Insulation Material:</b>	Glass Filled Nylon 46 - UL 94V-0 rated - Black (std)
<b>Heat Deflection:</b>	260°C @ 264 PSI per ASTM D648
<b>Insulation Resistance:</b>	5000 MegOhm @ 500VDC
<b>Current Rating:</b>	3 amps continuous @ 100 VDC/contact
<b>Max Processing Temp:</b>	250°C for 60 seconds
<b>Plastic:</b>	High Temperature Plastic
<b>INTERCONNECT SYSTEMS INC.</b>	
741 Flynn Road, Camarillo, Ca 93012 · (805) 482-2870 · fax (805) 482-8470 · e-mail: <a href="mailto:info@isipkg.com">info@isipkg.com</a>	